



# eni i-Base 15W-40

eni i-Base 15W-40 is a general-purpose oil formulated with top quality mineral oils suitable for spark-ignition and car diesel engines even when operating under the severest conditions involving, for instance, high-temperature motorway driving or low-temperature stop-go or taxi-service driving in towns.

## Characteristics (typical figures)

SAE Grade		15W-40
Viscosity at 100°C	mm <sup>2</sup> /s	14.5
Viscosity at 40°C	mm <sup>2</sup> /s	109
Viscosity at -20°C	mPa·s	6800
Viscosity Index	-	130
Flash Point COC	°C	210
Pour Point	°C	-24
Mass density at 15°C	kg/l	0.879

## Properties and performance

- eni i-Base 15W-40 has an extremely high Viscosity Index which keeps it free-flowing when cold and maintains high viscosity when hot. The same grade of lubricant can therefore be used in all seasons.
- Its superior detergent-dispersant properties effectively minimize the formation of lacquer and varnish, as well as other deposits, definitively avoiding the formation of the so called "black sludge".
- Its antiwear properties ensure long life for all moving parts, substantially reducing the need for engine servicing and overhauls.

## Specifications

eni i-Base 15W-40 is officially approved or meets the requirements of the following services and specifications:

- ACEA A3/B4-04
- API Service SL/CF
- MB 229.1
- VW 501 01 + 505 00